according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem KS-3000 Plus

Product code : 152.621

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings, Corrosion inhibitor

stance/Mixture

Recommended restrictions : Reserved for industrial and professional use.

on use professional use, Industrial use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH

Esinger Steinweg 50 25436 Uetersen

Germany

info@vosschemie.de

Telephone : 04122 717 0 Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0

sds@vosschemie.de

1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,

Göttingen, Deutschland

0551 19240

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. P243 Take action to prevent static discharges.

P261 Avoid breathing mist or vapours.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P312 Call a POISON CENTER/ doctor if you feel unwell.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regu-

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

lations.

Hazardous components which must be listed on the label:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hydrocarbons, C9, Aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No.	Classification	Concentration
	EC-No.		(% w/w)
	Index-No.		
	Registration number		
Hydrocarbons, C7, N-alkanes,	64742-49-0	Flam. Liq. 2; H225	>= 10 - < 25
Isoalkanes, cycloalkanes	927-510-4	Skin Irrit. 2; H315	
	01-2119475515-33	STOT SE 3; H336	
		(Central nervous	
		system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
Hydrocarbons, C7-C9, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 5 - < 10
isoalkanes, cyclics	920-750-0	STOT SE 3; H336	
	01-2119473851-33	(Central nervous	
		system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
Hydrocarbons, C6-C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 5 - < 10
isoalkanes, cyclics, <5% n-	921-024-6	Skin Irrit. 2; H315	
hexane	01-2119475514-35	STOT SE 3; H336	
		(Central nervous	
		system)	
		Asp. Tox. 1; H304	

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

		Aquatic Chronic 2; H411	
Hydrocarbons, C9, Aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 5 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

Move out of dangerous area.

Take off contaminated clothing and shoes immediately.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later. Show this safety data sheet to the doctor in attendance.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial respira-

tion.

Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water.

Call a physician if irritation develops or persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Keep eye wide open while rinsing. If easy to do, remove contact lens, if worn.

Consult a physician.

If swallowed : Do NOT induce vomiting.

Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Dry powder Water spray jet Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Build-up of dangerous/toxic fumes possible in cases of

fire/high temperature.

Hazardous combustion prod: :

ucts

Hazardous decomposition products due to incomplete com-

bustion

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire and/or explosion do not breathe fumes. In the event of fire, wear self-contained breathing apparatus. Use

personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.

Evacuate personnel to safe areas.

Ensure adequate ventilation, especially in confined areas.

Remove all sources of ignition.

Do not smoke.

Avoid contact with skin, eyes and clothing.

In the case of vapour formation use a respirator with an ap-

proved filter.

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages

cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.

Provide sufficient air exchange and/or exhaust in work rooms.

Wear personal protective equipment.

Use only in well-ventilated areas.

Advice on protection against

fire and explosion

Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not

smoke. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Store in original container. Keep containers tightly closed in a

dry, cool and well-ventilated place.

Further information on stor-

age conditions

Keep away from heat and sources of ignition. Protect from

moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes	Workers	Inhalation	Long-term systemic effects	2085 mg/m3
	Workers	Skin contact	Long-term systemic effects	300 mg/kg
	Consumers	Inhalation	Long-term systemic effects	447 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	149 mg/kg
Hydrocarbons, C7- C9, n-alkanes, isoal- kanes, cyclics	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber

Break through time : > 480 min
Glove thickness : >= 0.12 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

or heat-resistant synthetic fibres.

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Long sleeved clothing

Respiratory protection : Apply technical measures to comply with the occupational

exposure limits.

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release

(dust).

Filter type : Organic vapour type (A)

Protective measures : Ensure that eye flushing systems and safety showers are

located close to the working place. Avoid contact with the skin and the eyes. Use only with adequate ventilation.

Environmental exposure controls

Soil : Avoid subsoil penetration.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : white

Odour : characteristic

Melting point/freezing point : not determined

Initial boiling point and boiling

range

94 - 99 °C

Upper explosion limit / Upper :

flammability limit

7 %(V)

Lower explosion limit / Lower

flammability limit

1 %(V)

Flash point : -7 °C

Ignition temperature : > 200 °C

pH : not determined substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : 1,500 mPa.s (20 °C)

Viscosity, kinematic : not determined

Solubility(ies)

Water solubility : immiscible

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 60 hPa (20 °C)

Density : 1.04 g/cm3 (20 °C)

9.2 Other information

Explosives : Not explosive

In use, may form flammable/explosive vapour-air mixture.

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : None known.

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Acute oral toxicity : LD50 Oral (Rat): > 5,840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rat): > 2,800 - 3,100 mg/kg

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5,840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,800 - 3,100 mg/kg

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 Oral (Rat): > 5,840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 Dermal (Rat): > 2,800 - 3,100 mg/kg

Hydrocarbons, C9, Aromatics:

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3,492 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,160 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Result : Skin irritation

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Result : Skin irritation

Hydrocarbons, C9, Aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Germ cell mutagenicity- As- : Classified based on benzene content < 0.1% (Regulation (EC)

sessment 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- As- : Classified based on benzene content < 0.1% (Regulation (EC)

sessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Carcinogenicity - Assess: Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Assessment : May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or

dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 10

mg/l

End point: Growth rate Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 1,534 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4.6 - 10 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

End point: Growth rate Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 0.574 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 15.8 mg/l

End point: mortality

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Exposure time: 72 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

End point: Biomass Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 35.57 mg/l

End point: Growth rate Exposure time: 48 h

Toxicity to fish (Chronic tox-

icity)

NOELR: 2,045 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3.2 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 1.228 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOELR: 2.144 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

12.2 Persistence and degradability

Components:

Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes:

Biodegradability : Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 78 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-

octanol/water

: No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019 1.1 GB/EN 06.10.2021 Date of first issue: 28.10.2019

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Do not dispose of with domestic refuse.

Do not empty into drains, dispose of this material and its con-

tainer at hazardous or special waste collection point. Dispose of in accordance with local regulations. Send to a licensed waste management company.

Contaminated packaging Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of in accordance with local regulations.

Waste Code The following Waste Codes are only suggestions:

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN UN 1139 **ADR** UN 1139 **RID** UN 1139 **IMDG** UN 1139 IATA **UN 1139**

14.2 UN proper shipping name

ADN COATING SOLUTION

(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes,

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

ADR COATING SOLUTION

(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes,

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

RID COATING SOLUTION

> (Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

IMDG : COATING SOLUTION

(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

IATA : Coating solution

(Hydrocarbons, C7, N-alkanes, Isoalkanes, cycloalkanes, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADN

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

Remarks : Special Provision 640D

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

Remarks : Special Provision 640D

RID

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

Remarks : Special Provision 640D

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, <u>S-E</u>

IATA (Cargo)

Packing instruction (cargo : 364

aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Class 3 - Flammable liquids

IATA (Passenger)

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Packing instruction (passen: 353

ger aircraft)

Packing instruction (LQ) : Y341
Packing group : II

Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving

dangerous substances.

P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H335 : May cause respiratory irritation. H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard Flam. Liq. : Flammable liquids Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS -Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association: IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

according to Regulation (EC) No. 1907/2006



Carsystem KS-3000 Plus

Version Revision Date: Date of last issue: 28.10.2019
1.1 GB / EN 06.10.2021 Date of first issue: 28.10.2019

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Flam. Liq. 2 H225 Based on product data or assessment
Skin Irrit. 2 H315 Calculation method
STOT SE 3 H336 Calculation method

Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.