according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem KS-1000

Product code : 149.264

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Solvent-borne coatings, Corrosion inhibitor

stance/Mixture

Recommended restrictions

on use

Industrial use, professional use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH

Esinger Steinweg 50 25436 Uetersen

Germany

info@vosschemie.de

Telephone : 04122 717 0 Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0

sds@vosschemie.de

1.4 Emergency telephone number

Telephone : Giftinformationszentrum (GIZ)-Nord,

Göttingen, Deutschland

0551 19240

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Cat-

egory 2

H411: Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements

P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P260 Do not breathe mist or vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ eye protection/ face protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immedi-

ately all contaminated clothing. Rinse skin with water.

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P312 Call a POISON CENTER/ doctor if you feel unwell.

Storage:

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P410 + P412 Protect from sunlight. Do not expose to tem-

peratures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

#### Hazardous components which must be listed on the label:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

#### **Additional Labelling**

EUH211

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Chemical nature : Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	Not Assigned 920-750-0 01-2119473851-33	Flam. Liq. 2; H225 STOT SE 3; H336 (Central nervous system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 25 - < 50
Reaction mass of ethylbenzene and xylene	Not Assigned 905-588-0 01-2119486136-34, 01-2119488216-32	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315	>= 2.5 - < 10

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

		Eye Irrit. 2; H319 STOT SE 3; H335 (Respiratory system) STOT RE 2; H373 Asp. Tox. 1; H304	
Titanium dioxide	13463-67-7 236-675-5 01-2119489379-17	Carc. 2; H351	>= 1 - < 2.5

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

General advice : In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

Move out of dangerous area.

Take off contaminated clothing and shoes immediately.

Do not leave the victim unattended.

Symptoms of poisoning may appear several hours later. Show this safety data sheet to the doctor in attendance.

Protection of first-aiders : First Aid responders should pay attention to self-protection

and use the recommended protective clothing

If inhaled : Move to fresh air.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial respira-

tion.

Call a physician immediately.

In case of skin contact : Wash off immediately with soap and plenty of water.

Call a physician if irritation develops or persists.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

Keep eye wide open while rinsing.

If easy to do, remove contact lens, if worn.

Consult a physician.

If swallowed : Do NOT induce vomiting.

Call a physician immediately.

## 4.2 Most important symptoms and effects, both acute and delayed

Risks : May cause drowsiness or dizziness.

Repeated exposure may cause skin dryness or cracking.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Dry powder
Water spray jet

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Build-up of dangerous/toxic fumes possible in cases of

fire/high temperature.

Hazardous combustion prod- :

ucts

Hazardous decomposition products due to incomplete com-

bustion

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Further information : Use water spray to cool unopened containers.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.

Evacuate personnel to safe areas.

Ensure adequate ventilation, especially in confined areas.

Remove all sources of ignition.

Do not smoke.

Avoid contact with skin, eyes and clothing.

In the case of vapour formation use a respirator with an ap-

proved filter.

6.2 Environmental precautions

Environmental precautions : Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Do not flush into surface water or sanitary sewer system.

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

Local authorities should be advised if significant spillages

cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Do not flush with water.

#### 6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Keep container closed when not in use.

Provide sufficient air exchange and/or exhaust in work rooms.

Wear personal protective equipment.

Avoid formation of aerosol.

Advice on protection against

fire and explosion

Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic

charge. Use explosion-proof equipment.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Store in original container. Keep containers tightly closed in a

dry, cool and well-ventilated place.

Further information on stor-

age conditions

Keep away from heat and sources of ignition. Protect from

moisture. Keep away from direct sunlight.

Advice on common storage : Keep away from food and drink.

7.3 Specific end use(s)

Specific use(s) : No data available

### **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational Exposure Limits**

•				
Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
Titanium dioxide	13463-67-7	TWA (inhalable	10 mg/m3	GB EH40
		dust)		
		TWA (Respirable	4 mg/m3	GB EH40

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

dust)

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C7- C9, n-alkanes, isoal- kanes, cyclics	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg

#### 8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : >= 0.5 mm
Directive : DIN EN 374
Protective index : Class 6

Remarks : Gloves should be discarded and replaced if there is any indi-

cation of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

or heat-resistant synthetic fibres.

Long sleeved clothing

Respiratory protection : In case of inadequate ventilation wear respiratory protection.

Apply technical measures to comply with the occupational

exposure limits.

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release

(dust).

Filter type : Combined particulates and organic vapour type (A-P)

Protective measures : Do not breathe vapours or spray mist.

Ensure that eye flushing systems and safety showers are

located close to the working place.

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

Avoid contact with the skin and the eyes. Use only with adequate ventilation.

**Environmental exposure controls** 

Soil : Avoid subsoil penetration.

### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

Physical state : liquid

Colour : grey

Melting point/freezing point : No data available

Initial boiling point and boiling

range

98 - 140 °C

Upper explosion limit / Upper

flammability limit

Upper explosion limit

7 %(V)

Lower explosion limit / Lower

flammability limit

Lower explosion limit

0.7 %(V)

Flash point : 2 °C

pH : not determined substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : 8,000 mPa.s (20 °C)

Viscosity, kinematic : 30 mm2/s (40 °C)

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-

octanol/water

: No data available

Vapour pressure : 30 hPa (20 °C)

Density : 1.05 g/cm3 (20 °C)

9.2 Other information

Explosives : Not explosive

Explosive when mixed with oxidizing substances.

Self-ignition : not auto-flammable

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No decomposition if used as directed.

#### 10.2 Chemical stability

No decomposition if stored and applied as directed.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : None known.

### 10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

### **SECTION 11: Toxicological information**

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### **Acute toxicity**

Not classified based on available information.

### **Product:**

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

#### **Components:**

## Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Acute oral toxicity : LD50 Oral (Rat): > 5,840 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,800 - 3,100 mg/kg

### Reaction mass of ethylbenzene and xylene:

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

Acute oral toxicity : LD50 Oral (Rat): 3,523 - 4,000 mg/kg

Method: EC Directive 92/69/EEC B.1 Acute Toxicity (Oral)

Acute inhalation toxicity : LC50 (Rat, male): 6350 - 6700 ppm

Exposure time: 4 h
Test atmosphere: vapour

Method: Regulation (EC) No. 440/2008, Annex, B.2

Acute dermal toxicity : LD50 Dermal (Rabbit): 12,126 mg/kg

Titanium dioxide:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LD50 (Rat): > 6.8 mg/l

Exposure time: 4 h

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

**Product:** 

Result : Repeated exposure may cause skin dryness or cracking.

**Components:** 

Reaction mass of ethylbenzene and xylene:

Result : Skin irritation

Titanium dioxide:

Remarks : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Reaction mass of ethylbenzene and xylene:

Result : Moderate eye irritation

Titanium dioxide:

Remarks : Dust contact with the eyes can lead to mechanical irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

### **Components:**

Titanium dioxide:

Remarks : No known sensitising effect.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

**Components:** 

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

**Components:** 

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Reaction mass of ethylbenzene and xylene:

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Components:

Reaction mass of ethylbenzene and xylene:

Assessment : May cause damage to organs through prolonged or repeated

exposure.

**Aspiration toxicity** 

Not classified based on available information.

**Components:** 

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Reaction mass of ethylbenzene and xylene:

May be fatal if swallowed and enters airways.

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019 1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

#### 11.2 Information on other hazards

### **Endocrine disrupting properties**

**Product:** 

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

### **SECTION 12: Ecological information**

### 12.1 Toxicity

### **Components:**

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Toxicity to fish LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l

> End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4.6 - 10 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

End point: Growth rate Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 0.574 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOELR: 1 mg/l

Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

**Ecotoxicology Assessment** 

Toxic to aquatic life with long lasting effects. Chronic aquatic toxicity

Reaction mass of ethylbenzene and xylene:

Toxicity to fish LC50 (Fish): 2.6 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019 1.1 GB/EN 04.08.2021 Date of first issue: 04.11.2019

Toxicity to daphnia and other :

aquatic invertebrates

LC50 (Daphnia dubia (water flea)): 1 mg/l

Exposure time: 24 h

Method: OECD Test Guideline 202

EC50 (Daphnia dubia (water flea)): 165 mg/l

Exposure time: 24 h

Toxicity to algae/aquatic

plants

EC50 (algae): 2.2 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

IC50 (algae): 1 - 10 mg/l Exposure time: 72 h

EC50 (Bacteria): 1 - 10 mg/l Toxicity to microorganisms

**Ecotoxicology Assessment** 

Chronic aquatic toxicity This product has no known ecotoxicological effects.

Titanium dioxide:

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

#### 12.2 Persistence and degradability

#### **Components:**

### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

#### 12.3 Bioaccumulative potential

### **Components:**

### Reaction mass of ethylbenzene and xylene:

Partition coefficient: n-

octanol/water

: log Pow: 3.2 (20 °C)

### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

### 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

**Product:** 

Additional ecological infor-

mation

No data available

### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Do not empty into drains, dispose of this material and its con-

tainer at hazardous or special waste collection point. Dispose of in accordance with local regulations. Send to a licensed waste management company.

Contaminated packaging : Empty containers should be taken to an approved waste han-

dling site for recycling or disposal.

Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances

080299, wastes not otherwise specified

20 01 27, paint, inks, adhesives and resins containing hazard-

ous substances

### **SECTION 14: Transport information**

#### 14.1 UN number or ID number

ADN : UN 1139
ADR : UN 1139
RID : UN 1139
IMDG : UN 1139
IATA : UN 1139

14.2 UN proper shipping name

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

ADN : COATING SOLUTION

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, xylene)

ADR : COATING SOLUTION

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, xylene)

RID : COATING SOLUTION

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, xylene)

IMDG : COATING SOLUTION

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, xylene)

IATA : Coating solution

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, xylene)

### 14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA : 3

### 14.4 Packing group

#### **ADN**

Packing group : III
Classification Code : F1
Labels : 3

#### **ADR**

Packing group : III
Classification Code : F1
Labels : 3
Tunnel restriction code : (E)

#### **RID**

Packing group : III
Classification Code : F1
Hazard Identification Number : 33
Labels : 3

### **IMDG**

Packing group : III
Labels : 3
EmS Code : F-E, <u>S-E</u>

### IATA (Cargo)

Packing instruction (cargo : 366

aircraft)

Packing instruction (LQ) : Y344
Packing group : III

Labels : Class 3 - Flammable liquids

### IATA (Passenger)

Packing instruction (passen:

ger aircraft)

355

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

Packing instruction (LQ) : Y344
Packing group : III

Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:

Number on list 3

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

: Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c

FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: < 560 g/l VOC content for the product in a ready to use condition.

### 15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.
H351 : Suspected of causing cancer if inhaled.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox. : Acute toxicity

Aguatic Chronic : Long-term (chronic) aguatic hazard

Asp. Tox. : Aspiration hazard
Carc. : Carcinogenicity
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT RE : Specific target organ toxicity - repeated exposure STOT SE : Specific target organ toxicity - single exposure GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in

according to Regulation (EC) No. 1907/2006



## Carsystem KS-1000

Version Revision Date: Date of last issue: 04.11.2019
1.1 GB / EN 04.08.2021 Date of first issue: 04.11.2019

China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

### Classification of the mixture: Classification procedure:

Flam. Liq. 2 H225 Based on product data or assessment

STOT SE 3 H336 Calculation method Aquatic Chronic 2 H411 Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.